

MT-243003/NH

902 - 928 MHz 11.5 dBi H Pol Omni Antenna

Electrical

Regulatory Compliance	RoHS, CE 0682
Frequency	902 - 928 MHz
Gain	11.5 dBi typ 11 dBi min
VSWR	1.7:1 typ, 2:1 max
Azimuth Ripple	3.5 dB max
Polarization	Horizontal
Azimuth Beam Width	Omni
Elevation Beam Width	9.5° typ
Input Impedance	50 ohm
Input Power	20 W max
Lightning Protection	Direct Ground

Mechanical

Dimensions	1940 x 280 x 55 mm max
Weight	11.5 kg max
Connector	N-type Female
Radome	Plastic
Base Plate	Aluminum with chemical conversion coating

Environmental

Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 68-2-1	72 h	-55 °C	
High Temperature	IEC 68-2-2	72 h	+71 °C	
Temp. Cycling	IEC 68-2-14	1 h	-45 °C +70 °C	3 Cycles
Vibration	IEC 60721-3-4	30 min/axis		Random 4M5
Shock Mechanical	IEC 60721-3-4			4M5
Humidity	ETSI EN300-2-4 T4.1E	144 h		95%
Water Tightness	IEC 529			IP32
Flammability	UL 94			Class HB
Solar Radiation	ASTM G53	1000 h		
Salt Spray	IEC 68-2-11 Ka	500 h		
Ice And Snow				25 mm Radial
Wind Speed	Survival			220 Km/h
	Operation			160 Km/h
Wind Speed	Front Thrust			155.1 kg
Survival	Side Thrust			30.5 kg

This document and the information contained in it are proprietary and confidential to MTI. No person is allowed to copy reprint reproduce or publish any part of this document nor disclose its contents to others nor make any use of it nor allow or assist others to make any use of it, unless by the prior written express authorization of MTI and then only to the extent authorized.

11 Hamelacha st. Afek Industrial Park, Rosh-Ha'AYin 4809121 | Tel. +972.3.9008900 | Fax. +972.3.9008901