

MT-262025/TRLH/A

902 – 928 MHz 6.5 dBic Dual RHCP & LHCP Reader Antenna

Electrical

Regulatory Compliance	RoHS, CE 0682
Frequency	902 – 928 MHz
Gain	6 dBic min 6.5 dBic typ
VSWR	1.2:1 typ 1.35:1 max
3 dB Beam Width	Azimuth: 80° typ Elevation: 60° typ
Polarization	RHCP & LHCP
Axial Ratio at Boresight	1.5 dB max
F/B Ratio	-18 dB max
Port to Port Isolation	40 dB min , 45 dB typ
Input Impedance	50 ohm
Input Power	6 W max
Lightning Protection	DC Grounded

Mechanical

Dimensions L x W x D	500 x 200 x 30 mm max
Weight	1.8 Kg max
Connector	2 x TNC Female reverse polarity
Radome	Plastic
Base Plate	Aluminum with chemical conversion coating

Environmental

Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 68-2-1	72 h	-55 °C	
High Temperature	IEC 68-2-2	72 h	+71 °C	
Temp. Cycling	IEC 68-2-14	1 h	-45°C to +70°C	3 Cycles
Thermal Shock Non-Operating			-30°C to +70°C	Ramp 30°C/min
Humidity	ETSI EN300-2-4 T4.1E	144 h		95%
Water Tightness*	IEC 529			IP54
Dust Resistance*				IP54
Solar Radiation	ASTM G53	1000 h		
Ozone Resistance	ETSI 300			
Flammability	UL 94			Class HB
Salt Spray	IEC 68-2-11 Ka	500 h		
Quasi Random Vibration				20 g rms for 4 hours
Vehicle Vibration Operating	1g rms, 10-500 Hz, in 3 axis	6 hours total, 2 h in each axis.	Accelerated wear – an additional 50 h in worst case axis.	
Mechanical Shock Operating	10g, 11 msec, half sine pulse			

*IP67 available upon request

This document and the information contained in it are proprietary and confidential to MTI. No person is allowed to copy reprint reproduce or publish any part of this document nor disclose its contents to others nor make any use of it nor allow or assist others to make any use of it, unless by the prior written express authorization of MTI and then only to the extent authorized.

11 Hamelacha st. Afek Industrial Park, Rosh-Ha'AYin 4809121 | Tel. +972.3.9008900 | Fax. +972.3.9008901