

MT-404084/ND

3.3 – 3.8 GHz 17 dBi 90° Double Dual Slant Sector Antenna



Electrical

Frequency	3.3 – 3.8 GHz
Gain	17 dBi typ
VSWR	1.5 : 1 typ 2.0 : 1 max
-3 dB Azimuth Beam Width	90° typ
-3 dB Elevation Beam Width	5° typ
Polarization	Double Dual Slant ± 45°
Side lobes Level	- 12 dB typ
Cross Polarization	- 15 dB max, - 20 dB typ
F/B Ratio	- 30 dB typ
Port To Port Isolation	30 dB
Input Impedance	50 ohm
Input Power	50W CW
Lightning Protection	DC Grounded

Mechanical

Dimensions	900 x 215 x 90 mm max
Weight	3.0 kg max
Connector	4 x N-Type Female
Radome	Plastic
Base Plate	Aluminum with chemical conversion coating
Mechanical Down Tilt	0° to -10°

Environmental

Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 68-2-1	72 h	-55 °C	
High Temperature	IEC 68-2-2	72 h	+71 °C	
Temp. Cycling	IEC 68-2-14	1 h	-45 °C +70 °C	3 Cycles
Vibration	IEC 60721-3-4	30 min/axis		Random 4M5
Shock Mechanical	IEC 60721-3-4			4M5
Humidity	ETSI EN300-2-4 T4.1E	144 h		95%
Water Tightness	IEC 529			IP64
Solar Radiation	ASTM G53	1000 h		
Salt Spray	IEC 68-2-11 Ka	500 h	-	-
Ice And Snow				25 mm Radial
Wind Speed	Survival			220 Km/h
	Operation			160 Km/h
Wind Load (Survival):	Front Thrust			53.4 kg
	Side Thrust			17.4 kg

This document and the information contained in it are proprietary and confidential to mti. No person is allowed to copy reprint reproduce or publish any part of this document nor disclose its contents to others nor make any use of it nor allow or assist others to make any use of it, unless by the prior written express authorization of mti and then only to the extent authorized.

11 Hamelacha st. Afek Industrial Park, Rosh-Ha'ayin 4809121 | Tel. +972.3.9008900 | Fax. +972.3.9008901