

MT-484026/NH

5.15 – 5.875 GHz 15 dBi 60° Sector Antenna

Electrical

Regulatory Compliance	ETSI EN 302 085 v1.1.2 (2001-2002)		
Frequency	5.15 – 5.875 GHz		
Gain	15 dBi min		
VSWR	1.7:1 typ, 2:1 max		
12 dBi Azimuth Beam Width	ETSI EN 302 085 v1.1.2 CS1-CS3 60° -4°/+7°		
Polarization	Horizontal		
Elevation Beam Width	10° ±1°		
Side Lobes Level	-30 dB max @ 90°		
Elevation Null Fill below horizon	1 st Null	ETSI EN 302 085 v1.1.2 CS1-CS3 -15 dB min @ 10°	
	2 nd Null	ETSI EN 302 085 v1.1.2 CS1-CS3 -25 dB min @ 20°	
Cross Polarization	ETSI EN 302 085 v1.1.2 CS1-CS3 -24 dB max		
F/B Ratio	-30 dB max		
Input Impedance	50 ohm		
Input Power	6 W max		
Lightning Protection	DC Grounded		

Mechanical

Dimensions	436 x 250 x 10 mm max		
Weight	2.2 kg max		
Connector	N - type Female		
Radome	Plastic		
Base Plate	Aluminum with chemical conversion coating		

Environmental

Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 68-2-1	72 h	-55 °C	
High Temperature	IEC 68-2-2	72 h	+71 °C	
Temp. Cycling	IEC 68-2-14	1 h	-45 °C +70 °C	3 Cycles
Vibration	IEC 60721-3-4	30 min/axis		Random 4M5
Shock Mechanical	IEC 60721-3-4			4M5
Humidity	ETSI EN300-2-4 T4.1E	144 h		95%
Water Tightness	IEC 529			IP54
Solar Radiation	ASTM G53	1000 h		
Flammability	UL 94			Class HB
Salt Spray	IEC 68-2-11 Ka	500 h		
Ice And Snow				25 mm Radial
Wind Speed	Survival			220 Km/h
	Operation			160 Km/h
Wind Load	Front Thrust			31.4 kg
Survival	Side Thrust			1.3 kg

This document and the information contained in it are proprietary and confidential to MTI. No person is allowed to copy reprint reproduce or publish any part of this document nor disclose its contents to others nor make any use of it nor allow or assist others to make any use of it, unless by the prior written express authorization of MTI and then only to the extent authorized.