

MT-951004

30 – 1200 MHz Airborne DF Blade Antenna



Electrical

Frequency	30 – 1200 MHz																				
Gain	<table border="1"> <tr> <td>MHz</td> <td>30</td> <td>34</td> <td>60</td> <td>88</td> <td>108</td> <td>136</td> <td>174</td> <td>225</td> <td>400 - 1200</td> </tr> <tr> <td>dBi</td> <td>-28</td> <td>-27</td> <td>-21</td> <td>-14</td> <td>-10</td> <td>-3</td> <td>0</td> <td>1</td> <td>>0</td> </tr> </table>	MHz	30	34	60	88	108	136	174	225	400 - 1200	dBi	-28	-27	-21	-14	-10	-3	0	1	>0
MHz	30	34	60	88	108	136	174	225	400 - 1200												
dBi	-28	-27	-21	-14	-10	-3	0	1	>0												
VSWR	2.6:1 max @100 – 1200 80% of the band 3.5:1 max @ 100 – 1200 20% of the band 3:1 max @ 30 – 100																				
Azimuth	Omni																				
Ripple	± 2 dB @ 30 – 500 MHz ± 2.5 dB @ 500 – 1200 MHz																				
Polarization	Vertical																				
Phase Tracking	± 3 dB @ 30 – 150 MHz ± 4 dB @ 150 – 1200 MHz																				
Monotonic Phase Tracking	No fast ripple change. Less than 12 sine waves over 30 – 1200 MHz																				
Input impedance	50 Ω																				
Input Power	10 W CW 1KW peak																				
Lightning Protection	DC Grounded																				
Monitor Probe (BIT)	TNC located at antenna base coupled to the main input > -60 dB coupling																				
Amplitude matching between Probes																					

Mechanical

Dimensions LxWxD	327 x 317.5 x 118.4 mm max
Weight	2.1 Kg max
Connector	TNC Female
Radome	Fiberglass
Color	Polyurethane per MIL-C-83286 GRAY 36375 PER FED-STD-595
Base Plate	Aluminum with chemical conversion coating

Environmental

Test	Standard	Duration	Temperature	Notes
Low Temperature	MIL-STD-810E Method 501.3 Proc. I & II	24 h	-54° C	
High Temperature	MIL-STD-810E Method 501.3 Proc. I & II	96 h	+85° C	
Temperature/Altitude	MIL-STD-810C Method 504.2 Proc. I	33 h	-57° to 85° C	40,000 ft
Temperature Shock	MIL-STD-810E Method 503.3	2 h	-45° to 85° C	3 Cycles
Vibration	MIL-STD-810D Method 514.3 Cat. 4	3 X 1 h/axis	Li=0.6g ² /Hz F1 68 Hz	
Shock	MIL-STD-810D Method 516.4 Proc. I	11 msec/axis		3 x 20 g/axis
Humidity	MIL-STD-810E Method 507.3 Proc. I 98% @ 45°	240 h	98% 10 cycles of 24 h	
Salt Spray	MIL-STD-810E Method 509.3 Proc. I	48 h	5% Nacl	
Side Pressure			6 PSI	
Sand	MIL-STD-810E Method 510.3 Proc. II			
Dust	MIL-STD-810E Method 510.3 Proc. I			
Solar Radiation	MIL-STD-810E Method 505.3 Proc. I		7 cycles of 24 h	
Acceleration	MIL-STD-810E Method 513.4 Proc. I			13.5 g all axis
Rain		30 mm	10cm/hr 18m/sec Each side	
Fungus	MIL-STD-810E Method 508.4			
Endurance	MIL-STD-810D Method 514.4 Fig. 514.4-7 a	3 X 1 h/axis	L1=2.4 g ² /Hz F1=687 Hz	
Wind Speed		0.85 mach @ sea level		

This document and the information contained in it are proprietary and confidential to MTI. No person is allowed to copy reprint reproduce or publish any part of this document nor disclose its contents to others nor make any use of it nor allow or assist others to make any use of it, unless by the prior written express authorization of MTI and then only to the extent authorized.

11 Hamelacha st. Afek Industrial Park, Rosh-Ha'ayin 4809121 | Tel. +972.3.9008900 | Fax. +972.3.9008901