

# MT006D11VH

470–700 MHz 11 dBi Directional Antenna



## Electrical

Regulatory Compliance	RoHS, CE 0682
Frequency	470 – 700 MHz
Gain	9.6 dBi @ 470 MHz 11 dBi @ 585 MHz 12 dBi @ 700 MHz
VSWR	1.7:1 typ, 2:1 max
Polarization	Dual linear Vertical & Horizontal
3 dB Beam width	55° @ 470 MHz 46° @ 585 MHz 40° @ 700 MHz
Side lobe Level	15 dB typ
Port To Port Isolation	30 dB
Front to Back Ratio	18 dB min
Input Impedance	50 Ω
X Pol Level	25 dB
Power handling	10 W CW
Lightning Protection	DC grounded

## Mechanical

Dimensions	600 x 600 x 111 mm max
Weight	6 Kg max
Connector	2 x N-Type Female
Radome	Plastic
Base Plate	Aluminum with chemical conversion coating

## Environmental

Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 68-2-1	72 h	-45°C	
High Temperature	IEC 68-2-2	72 h	+71°C	
Temp. Cycling	IEC 68-2-14	1 h	-45°C +70°C	3 Cycles
Vibration	IEC 60721-3-4	30 min/axis		Random 4M5
Shock Mechanical	IEC 60721-3-4			4M5
Humidity	ETSI EN300-2-4 T4.1E	144 h		95%
Water Tightness	IEC 529			IP67
Solar Radiation	ASTM G53	1000 h		
Salt Spray	IEC 68-2-11 Ka	500 h		
Ice And Snow				25 mm Radial
Wind Speed Survival Operation				220 Km/h 160 Km/h
Wind Load Survival Front Thrust				123.4 kg
Side Thrust				21.3 kg

This document and the information contained in it are proprietary and confidential to MTI. No person is allowed to copy reprint reproduce or publish any part of this document nor disclose its contents to others nor make any use of it nor allow or assist others to make any use of it, unless by the prior written express authorization of MTI and then only to the extent authorized.

11 Hamelacha st. Afek Industrial Park, Rosh-Ha'AYin 4809121 | Tel. +972.3.9008900 | Fax. +972.3.9008901