

MT009R09LH

Ant. 902-928 MHz 9.5dBic RFID Antenna

Electrical

Regulatory Compliance	RoHS, CE 0682
Frequency	902 – 928 MHz
Gain	10 dBic typ
VSWR	2.0:1
3 dB Beam Width	Azimuth: 75° typ Elevation: 30° typ
Polarization	Circular LHCP
Axial Ratio	3 dB typ
Input Impedance	50 ohm
Input Power	6 W max
Lightning Protection	DC Grounded

Mechanical

Dimensions L x W x D	900 x 300 x 8 mm
Weight	2.7 Kg
Interface	Cable RG316 length 300 mm
Connector	SMA
Radome	Plastic
Mounting	No

Environmental

Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 68-2-1	72 h	-45 °C	
High Temperature	IEC 68-2-2	72 h	+71 °C	
Temp. Cycling	IEC 68-2-14	1 h	-45°C to +70°C	3 Cycles
Humidity	ETSI EN300-2-4 T4.1E	144 h		95%
Water Tightness	IEC 529			IP54
Static Load				250 kg on area of 300 cm ²

This document and the information contained in it are proprietary and confidential to MTI. No person is allowed to copy reprint reproduce or publish any part of this document nor disclose its contents to others nor make any use of it nor allow or assist others to make any use of it, unless by the prior written express authorization of MTI and then only to the extent authorized.

11 Hamelacha st. Afek Industrial Park, Rosh-Ha'Ayin 4809121 | Tel. +972.3.9008900 | Fax. +972.3.9008901