

MT026S18DS

2.5 – 2.7 GHz 18 dBi 45° Double Dual Slant Sector Antenna

Electrical

Regulatory Compliance	RoHS, CE 0682
Frequency	2.5 – 2.7 GHz
Gain	18.0 dBi min
VSWR	1.5:1 typ, 2:1 max
15 dBi Azimuth Beam Width	45° typ
-3 dB Elevation Beam Width	7° typ
Polarization	Double Dual Slant
Cross Polar Discrimination	-13 dB max
Elevation Side Lobes Level	-13 dB typ
Azimuth Side Lobes Level	15 dBi min @ ±22.5° -12 dB max @ ±45° -23 dB max @ ±60° -25 dB @ ±90°
F/B Ratio	-25 dB max
Port to Port Isolation	25 dB min - Same antenna 30 dB min - Between antennas
Input Impedance	50 Ω
Input Power	50 W CW 200 W max @ 5uSec
Lightning Protection	DC Grounded

Mechanical

Dimensions	880 x 390 x 95 mm max
Weight	5.5 kg max
Connector	4 x N- Type Female
Base Plate	Aluminum with chemical conversion coating

Environmental

Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 68-2-1	72 h	-55 °C	
High Temperature	IEC 68-2-2	72 h	+71 °C	
Temp. Cycling	IEC 68-2-14	1 h	-45 °C +70 °C	3 Cycles
Vibration	IEC 60721-3-4	30 min/axis		Random 4M5
Shock Mechanical	IEC 60721-3-4			4M5
Humidity	ETSI EN300-2-4 T4.1E	144 h		95%
Water Tightness	IEC 529			IP64
Solar Radiation	ASTM G53	1000 h		
Salt Spray	IEC 68-2-11 Ka	500 h		
Ice And Snow				25 mm Radial
Wind Speed	Survival			220 Km/h
	Operation			160 Km/h
Wind Load	Front Thrust			117.6 kg
Survival	Side Thrust			26.7 kg

This document and the information contained in it are proprietary and confidential to MTI. No person is allowed to copy reprint reproduce or publish any part of this document nor disclose its contents to others nor make any use of it nor allow or assist others to make any use of it, unless by the prior written express authorization of MTI and then only to the extent authorized.