

# MT2406M09DS/4

2.4 – 2.5, 5 – 7.15 GHz 4x4 Access WIFI

## Electrical

Regulatory Compliance	RoHS , CE 0682	
Frequency Range	2.4 – 2.5 GHz	5 – 7.15 GHz
Polarization	Dual slant $\pm 45^\circ \times 2$	
Gain without cable	7.0 dBi	7.0-8.0 dBi
Gain with cable	7.0 $\pm$ 0.5 dBi	5.0-7.0 @ 1.0 $\pm$ 7.0 6.0 $\pm$ 0.7 @ 7.0-7.15
VSWR	2.0: 1	
-3 dB Beam Width Azimuth	70° typ	56° typ
-3 dB Beam Width Elevation	70° typ	56° typ
Port to Port Isolation	20 dB	20 dB
Cross Polarization	9 dB	9 dB
Input Impedance	50 ohm	
Input Power	6 W max	
Lightning Protection	DC Grounded	

## Mechanical

Dimensions	190 x 190 x 40mm max Additional 11 mm on each side is required for antenna wall installation
Weight	1.0 kg max
Connector	4 x SMA Reverse Polarity with 750 mm cable
Radome	Plastic RAL-9002
Base Plate	Plastic

## Environmental

Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 68-2-1	72 h	-40 °C	
High Temperature	IEC 68-2-2	72 h	+85 °C	
Vibration	IEC 60721-3-4	30 min/axis		Random 4M3
Shock Mechanical	IEC 60721-3-4			4M3
Humidity	ETSI EN300-2-4 T4.1E	144 h		95%
Water Tightness	IEC 529			IP67
Solar Radiation	ASTM G53	2000 h		
Flammability	UL 94			CLASS V2
Salt Spray	IEC 68-2-11 Ka	200 h		
Wind Speed	Survival			220 Km/h
	Operation			160 Km/h
Wind Load	Front Thrust			10.3 kg
Survival	Side Thrust			2.2 kg

This document and the information contained in it are proprietary and confidential to Mti. No person is allowed to copy reprint reproduce or publish any part of this document nor disclose its contents to others nor make any use of it nor allow or assist others to make any use of it, unless by the prior written express authorization of Mti and then only to the extent authorized.